

## TECHNICAL DATA SHEET

Order No. 323-10911

Item/Model SARO Pizza preparation table with

drawers

model MARGA PZ 1610 TN

GTIN 4017337038589





- Material: (housing and interior) stainless steel; (worktop with upstand) granite
- 1 self-closing door + 7 drawers (uncooled)
- Upstand: max. height 150 mm
- 7 sets of support rails
- Supplied without grids (grid 400 x 600 mm, optionally available: 323-5150)
- Optional cooling attachment available:

VRX 1500/330 (order no. 323-1136) or VRX 1500/380 (323-1034)

- Extractable compressor for easy cleaning
- Digital temperature control (DIXELL)
- Insulation: 60 mm
- Forced air cooling
- Automatic defrost
- Temperature range: +2 / +8 °C
- Connection: 230 V 50 Hz 0.350 kW
- Capacity (gross/net): 221/127 liters
- Internal dimensions: W 435 x D 680 x H 560 mm (door only)
- External dimensions: W 1515 x D 800 x H 890-950/1040 mm
- 4 adjustable feet
- Weight: 291.5 kg
- Refrigerant: R600a
- Energy efficiency class: C (spectrum A+++ to E)
- Sound level: approx. 40dB(A)

Origin China customs tariff no. 84185090

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



## SAFETY & WARNING INSTRUCTIONS

Order No. 323-10911

Item/Model SARO Pizza preparation table with

drawers

model MARGA PZ 1610 TN

GTIN 4017337038589





## Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY