

TECHNICAL DATA SHEET

Order No. 323-4605
Item/Model SARO Chest Freezer
model BD 501 S
GTIN 4017337071142



- Material: (housing) steel, white powder-coated, (interior) Aluminum, (Lid) stainless steel
- Baskets: 2 x W 330 x D 544 x H 320 mm
- 4-star compartment, suitable for freezing, up to 12 months storage
- Digital temperature control (DIXELL)
- Insulation: 90 mm
- Cooling type: Static cooling
- Manual defrost
- Suitable for climate class: 4, 5
- Temperature range: <-18°C
- 4 wheels, H 83 mm
- Connection: 230 V - 50 Hz - 0.190 kW
- Capacity (gross/net): 516 / 514 L
- Inner dimensions: W 1646 x D 501 x H 675.5 mm
- Outer dimensions: W 1835 x D 730 x H 970 mm
- Weight (net/gross): 89 / 105 kg
- Refrigerant R600a
- Energy efficiency class: E (spectrum A to G)

Origin China
customs tariff no. 84181020
Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-4605
Item/Model SARO Chest Freezer
model BD 501 S
GTIN 4017337071142



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block or cover ventilation slots and openings to ensure proper air circulation and prevent overheating.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Use only original spare parts and accessories approved for the device.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Always switch off the device and unplug it from the power supply before cleaning, maintenance, or extended periods of non-use.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.
- Do not place heavy objects on the device to avoid deformation or damage.
- Keep the power plug easily accessible to quickly disconnect the device from the power supply in case of emergency.

Origin China
customs tariff no. 84181020
Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827