

TECHNICAL DATA SHEET

Order No. 323-4445

Item/Model SARO Freezer
model HT 600I S/S

GTIN 4017337071777



- Material: (housing and interior) stainless steel
- 3 shelves: W 654 x D 525 mm, adjustable in height, 1 bottom shelf: W 654 x D 330 mm
- Lockable
- Digital temperature control (DIXELL)
- Insulation: 60mm
- Air circulation cooling
- Automatic defrosting
- Suitable for climate class: 4
- Temperature range: < -18 °C
- 2 feet + 2 castors
- Connection: 230 V / 50 Hz / 0.270 kW
- Capacity (gross/net): 620 / 411 L
- Internal dimensions: W 657 x D 580 x H 1660 mm
- External dimensions: W 777 x D 745 x H 1895 mm
- Weight (net/gross): 90 / 97 kg
- Refrigerant R290
- Energy efficiency class: C (spectrum from A+++ to E)

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-4445

Item/Model SARO Freezer
model HT 600I S/S

GTIN 4017337071777



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating and inefficient cooling.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- The refrigerant is flammable; avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames.
- After transporting or tilting the device significantly, let it stand upright for at least 24 hours before switching it on.
- Before cleaning, switch off the device, unplug it, and allow it to fully defrost.
- Never clean the device with a water jet.
- Maintenance and repair work must only be carried out by qualified personnel.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- After power outages or disconnection from the power supply, wait at least 5 minutes before restarting the device.
- Keep the door open only as long as necessary to minimize energy loss and maintain cooling efficiency.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827