

saro

TECHNICAL DATA SHEET

Order No. 481-1075

Item/Model SARO Ice cream/freezer

model EL 71

GTIN 4017337065325



- Material: (housing + interior) steel, powder-coated, white;
 (hinged lid) plastic, white, foamed inside
- Hinged lid insulated, lockable
- Chest freezer designed for packed ice crem (can also be used for other foods)
- 3 mesh baskets for hanging included (6 possible)
- Delivery ready to plug in (Schukoplug type F)
- Optional chest with wheels and/or digital, integrated thermometer available
- Manual temperature control (outside, front)
- Insulation: 60 mm
- Static cooling
- Manual defrost
- Suitable for ambient temperatures from +16 to +30 °C
- Temperature range: -16/ -22 °C
- Connection: 230 V 50 Hz 0.245 kW
- Volume (gross/net): 691 / 564 liters
- Internal dimensions: W 1686 x D 576 x H 741 mm
- External dimensions: W 1805 x D 695 x H 865 mm
- 4 feet, levelable
- Weight (net/gross): 85 / 89 kg
- Refrigerant: R600a
- Energy efficiency class: D (spectrum A to G)
- More options:
- * different types of baskets
- * Separation/sorting aids

Origin Denmark customs tariff no. 84181080

Stand: 06.03.2025

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



SAFETY & WARNING INSTRUCTIONS

Order No. 481-1075

Item/Model SARO Ice cream/freezer

model EL 71

GTIN 4017337065325





Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block or cover ventilation slots and openings to ensure proper air circulation and prevent overheating.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Use only original spare parts and accessories approved for the device.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Always switch off the device and unplug it from the power supply before cleaning, maintenance, or extended periods of non-use.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.
- Do not place heavy objects on the device to avoid deformation or damage.
- Keep the power plug easily accessible to quickly disconnect the device from the power supply in case of emergency.

Origin Denmark customs tariff no. 84181080

Stand: 06.03.2025

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY