

TECHNICAL DATA SHEET

Order No. **323-1425**

Item/Model **SARO Commercial Refrigerator, 2-door, 2/1
model GN 1410 TN PRO**

GTIN **4017337068043**



- **Material:** (housing) stainless steel AISI 430, (interior) stainless steel AISI 304
- **2 doors, self-closing, lockable, with practical magnetic seal**
- **6 adjustable shelves:** W 530 x D 650 mm, load capacity per shelf: 25 kg
- **Shelf adjustment:** Up to 80 mm spacing possible
- **Various shelf insertion options through notches in the side wall**
- **2 bottom shelves (W 538 x D 630 mm) for optimal, energy-reducing air circulation**
- **4 height adjustable feet**
- **Digital temperature control (DIXELL)**
- **Insulation: 90 mm**
- **Circulating air cooling with highly efficient fan and optimal air guidance**
- **Automatic fan shutdown system when door is opened**
- **Automatic defrosting and automatic evaporation of condensation water**
- **Suitable for climate class 4, 5**
- **Temperature range: -2 / +8 °C**
- **Connection: 230 V - 50 Hz - 0.130 kW**
- **Shelves: 3x W 530 x D 650 mm + for bottom: W 510 x D 605 mm**
- **Capacity (gross/net): 1300 / 940 liters**
- **interior dimensions: W 1240 x D 700 x H 1501 mm**
- **Exterior dimensions: W 1420 x D 875 x H 2090 mm**
- **Weight (net/gross): 198 / 213 kg**
- **Refrigerant: R600a**
- **Energy efficiency class: A (spectrum A+++ to G) with climate class**
-> high-performance device!

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-1425**

Item/Model **SARO Commercial Refrigerator, 2-door, 2/1
model GN 1410 TN PRO**

GTIN **4017337068043**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827