

TECHNICAL DATA SHEET

Order No. 437-1006

Item/Model SARO Bottle cooler with canopy
model GTK 282 M

GTIN 4017337048014



- Material: (housing) steel enamel, white;
(interior) plastic, white;
(glass door frame) plastic, black
- With billboard - white neutral display installed
(color display with Saro logo included as replacement)
- Door lockable, self-closing, double glass
- 4 adjustable grids
- LED-lighting, interior and billboard can be switched
on separately
- Analog Temperature Control
- Static cooling with circulation fan
- Temperature range: 0 / +10 °C
- Connection: 230 V - 50 Hz - 0.225 kW
- Grids: 4x W 422 x D 380 mm
- Capacity (gross/net): 282/260 liters
- External dimensions: W 530 x D 590 x H 1845 mm
- 2 height-adjustable feet at the front,
2 swivel wheels at the back
- Weight: 70 kg
- Refrigerant: R600a
- Energy efficiency class: D (spectrum A to G)

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 437-1006

Item/Model SARO Bottle cooler with canopy
model GTK 282 M

GTIN 4017337048014



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or tilting the device over 45 degrees, allow it to stand upright for at least 24 hours before switching it on to avoid damage to the cooling system.
- Do not block ventilation slots or openings to ensure optimal air circulation and cooling.
- Do not operate the device near heat sources or in direct sunlight.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances in the device.
- Never clean the device with a water jet or immerse it in liquids to avoid the risk of short circuits and electric shock.
- Do not place hot food or uncovered liquids inside the device to prevent condensation or icing problems.
- Do not use damaged cables or plugs; replacement must be performed only by qualified personnel.
- Always switch off the device and disconnect it from the power supply before cleaning, maintenance, or extended periods of non-use.
- The device is intended exclusively for cooling and storing beverages or food; any other use may cause damage and void the warranty.
- The refrigerant is flammable; in case of damage to the cooling circuit, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to avoid damage to the compressor.
- Repairs and maintenance must only be carried out by qualified personnel.
- During transport, ensure the device's feet do not damage the power cord.
- Immediately stop operation if visible damage or malfunctions occur, and contact qualified personnel.
- Handle the glass door with care. Do not lean heavy objects against it or strike it. If cracks or damage are visible, do not use the door and have it replaced immediately by qualified personnel.
- Use only mild cleaning agents for cleaning, and clean the condenser at least monthly to prevent dust buildup.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827