

TECHNICAL DATA SHEET

Order No. 323-3126

Item/Model SARO Top Loading Bottle Cooler
model FKT 935

GTIN 4017337036950



Material: (housing) enamelled steel, white; (lid) stainless steel; (interior) light metal

- Insulated sliding lid, lockable
- Bottle opener with container
- Digital temperature control (DIXELL)
- Insulation: 40 mm
- Static cooling with fan support
- Automatic evaporator defrost
- Temperature range: +2 / +10 °C
- Connection: 230 V - 50 Hz - 0.300 kW
- Capacity (gross/netto): 279 / 152 liters
- Internal dimensions: W 824 x D 583 x H 445 mm
- External dimensions: W 935 x D 687 x H 888 mm
- 4 castors, 2 lockable
- Weight: 100kg
- Refrigerant: R600a
- Energy efficiency class: B (spectrum A+++ to E)

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-3126

Item/Model SARO Top Loading Bottle Cooler
model FKT 935

GTIN 4017337036950



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block or cover ventilation slots and openings to ensure proper air circulation and prevent overheating.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Use only original spare parts and accessories approved for the device.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Always switch off the device and unplug it from the power supply before cleaning, maintenance, or extended periods of non-use.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.
- Do not place heavy objects on the device to avoid deformation or damage.
- Keep the power plug easily accessible to quickly disconnect the device from the power supply in case of emergency.

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827