

TECHNICAL DATA SHEET

Order No. **323-2122**

Item/Model **SARO Freezers black
model HT 200 B**

GTIN **4017337055616**



- Material: (housing) steel stove-enamelled, black; (interior) plastic, white
- Door lockable
- Door stop changeable
- 3 evaporator grids, fixed (3 compartments)
- Digital temperature control (DIXELL)
- Static cooling
- Manual defrost
- Temp. -10 / -25 °C
- Connection: 230 V - 50 Hz - 0.150 kW
- Grids (fixed): 3x W 431 x D 415 mm
- Volume: 129 liters
- Internal dimensions: W 510 x 485 x 620 mm
- External dimensions: W 600 x D 585 x H 855 mm
- 2 adjustable feet + 2 castors (rear)
- Weight: 58kg
- Refrigerant: R600a

Origin China

customs tariff no. 84181080

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-2122**

Item/Model **SARO Freezers black
model HT 200 B**

GTIN **4017337055616**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating and inefficient cooling.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- The refrigerant is flammable; avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames.
- After transporting or tilting the device significantly, let it stand upright for at least 24 hours before switching it on.
- Before cleaning, switch off the device, unplug it, and allow it to fully defrost.
- Never clean the device with a water jet.
- Maintenance and repair work must only be carried out by qualified personnel.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- After power outages or disconnection from the power supply, wait at least 5 minutes before restarting the device.
- Keep the door open only as long as necessary to minimize energy loss and maintain cooling efficiency.

Origin China

customs tariff no. 84181080

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827