

TECHNICAL DATA SHEET

Order No. 323-2215

Item/Model SARO Refrigerator
model HK 400 PRO

GTIN 4017337071005



- Material: (housing) steel, powder-coated, white; (interior) plastic, white
- Lockable door
- Reversible door hinge
- Newly designed air circulation provides better airflow for more uniform temperature
- Automatic fan shutdown system to reduce cold loss and energy consumption
- 4 adjustable shelves, 3x W 502 x D 440 mm + 1x W 502 x D 211 mm
- Digital temperature control (DIXELL)
- Static cooling with circulation fan
- Automatic defrost
- Temperature range: -2 / +8 °C
- Connection: 230 V - 50 Hz - 0.08 kW
- Capacity (gross/net): 361 / 239 liters
- Internal dimensions: W 510 x D 485 x H 1620 mm
- External dimensions: W 600 x D 635 x H 1855 mm
- Weight (net/gross): 77 / 82 kg
- Refrigerant: R600a
- Energy efficiency class: A (spectrum A+++ to E)

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-2215

Item/Model SARO Refrigerator
model HK 400 PRO

GTIN 4017337071005



Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- After transport or significant tilting, leave the device upright for at least 24 hours before turning it on to avoid damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unattended near the device.
- Do not store flammable, explosive, or chemical substances in the device.
- Ventilation slots and openings must not be blocked to prevent overheating.
- Never immerse the device in water or clean it with a water jet; risk of short circuits and electric shock.
- If visible damage or malfunctions occur, immediately stop operation and contact the dealer.
- Do not place hot food or open liquids in the device to avoid condensation or freezing issues.
- Only use original spare parts and accessories that are approved for the device.
- Clean only when the device is switched off and unplugged.
- The device is exclusively intended for storing and cooling food; other uses may cause damage and void the warranty.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- After a power failure or briefly disconnecting the power cord, wait at least 5 minutes before turning the device back on to avoid damage to the compressor.
- Repairs and maintenance should only be carried out by qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827