

TECHNICAL DATA SHEET

Order No. **330-1012**

Item/Model **SARO Refrigerated Showcase
model SC 100 weiß**

GTIN **4017337330393**



- Material: (housing) plastic, white
- Double glazing on 4 sides
- Door and controls opposite
- 4 height-adjustable grids, plastic coated
- LED-interior-lighting, separately switchable
- Door stop on the right, not interchangeable
- Digital temperature control
- Automatic defrost
- Forced air cooling with fan
- Temperature range: 0 / +12 °C
- Connection: 230 V - 50 Hz - 0.180 kW
- Grids: 4x W 357 x D 310 mm
- Capacity: 98 liters
- Internal dimensions: W 367 x D 305 x H 785 mm
- External dimensions: W 428 x D 386 x H 1110 mm
- Weight (net/gross): 38 / 40.5 kg
- Refrigerant: R600a
- Energy efficiency class: C (spectrum A to G)

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **330-1012**

Item/Model **SARO Refrigerated Showcase
model SC 100 weiß**

GTIN **4017337330393**



Safety and Warning Instructions

- Only place the device on a stable, level, and non-slip surface.
- Ensure the mains voltage matches the specifications on the rating plate.
- All packaging materials and protective films must be completely removed before first use.
- After transport, let the device stand upright for at least 12 hours before switching it on to prevent damage to the refrigerant circuit.
- Ensure the ventilation slots are not blocked to maintain optimal air circulation and cooling.
- Do not place the device near heat sources or in direct sunlight.
- Bottles with high alcohol content must be tightly sealed and stored upright in the device.
- Do not use electrical devices or heating sources inside the appliance.
- Never clean the device with a water jet or high-pressure cleaner to avoid the risk of electric shock and short circuits.
- Do not use damaged cables or plugs. Replacement must only be carried out by qualified personnel.
- Always switch off the device and disconnect it from the power supply before cleaning, maintenance, or repairs.
- Clean the door seal with water only and ensure it remains intact to prevent energy loss.
- The refrigerant is flammable; if the cooling circuit is damaged, ventilate the room well and avoid open flames.
- Children must not use the device unsupervised or play near it.
- The device is intended solely for the storage of food; any other use may cause damage and void the warranty.
- Regular cleaning of the condenser by qualified personnel is recommended to extend the device's lifespan.
- Handle the display case with care (fragile glass). Do not lean heavy objects against it or strike it.
- If visible damage or malfunctions occur, immediately stop operation and contact qualified personnel.

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry

ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827