

TECHNICAL DATA SHEET

Order No. **330-3750**

Item/Model **SARO Wine Cooler
model WK 81**

GTIN **4017337068821**



- **Material: Glass with vertical stainless steel trim**
- **Elegant, slightly curved door, double-tempered glass**
- **Equipped with an inverter compressor, adjusting performance based on cooling demand**
- **Digital control**
- **Insulation: 45 mm**
- **9 shelves for approximately 81 standard bottles**
- **LED lighting, separately switchable**
- **Air circulation cooling**
- **Automatic defrosting**
- **4 wheels, 2 lockable**
- **Temperature range: +5 / +18 °C**
- **Connection: 230 - 240 V - 50 Hz - 0.500 kW**
- **Capacity: 400 L**
- **Exterior dimensions: W 656 x D 653 x H 1892 mm**
- **Weight (net/gross): 181 / 204 kg**
- **Refrigerant: R290**
- **Energy efficiency class: B (Scale A to G)**

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **330-3750**

Item/Model **SARO Wine Cooler
model WK 81**

GTIN **4017337068821**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827