



**MOD : CBT51/EV**

**Production code : LF05TE-M24T**

**07/2025**

Fiche technique / Scheda tecnica / Ficha técnica / Technisches Datenblatt /  
Technical datasheet / Technisch gegevensblad



## Dati tecnici

## Technical Data

|                                      |                                     |                      |
|--------------------------------------|-------------------------------------|----------------------|
| DIMENSIONI (L x P x H)               | DIMENSIONS (L x P x H)              | 790 x 700 x 875 mm   |
| CON IMBALLO (L x P x H)              | WITH EMBALLAGE (L x P x H)          | 810 x 720 x 1020 mm  |
| LARGHEZZA LUCE PORTA                 | WIDTH DOOR LIGHT                    | 680 mm               |
| ALTEZZA LUCE PORTA                   | HEIGHT DOOR LIGHT                   | 380 mm               |
| PROFONDITÀ INTERNA                   | INTERIOR DEPTH                      | 415 mm               |
| SPESSORE                             | THICKNESS                           | 60 mm                |
| CLASSE CLIMATICA                     | CLIMATE CLASS                       | 4                    |
| CAPACITÀ ABBATTIMENTO                | BLAST CHILLING CAPACITY             | 18 Kg                |
| CAPACITÀ CONGELAMENTO                | FREEZING CAPACITY                   | 12 Kg                |
| CAPACITÀ REFRIGERAZIONE <sup>1</sup> | REFRIGERATION CAPACITY <sup>1</sup> | 1416 W               |
| POTENZA ELETTRICA                    | POWER INPUT                         | 815 W                |
| ALLESTIMENTO CATERING                | CATERING LAYOUT                     | 5 GN1/1              |
| ALLESTIMENTO BAKING                  | BAKING LAYOUT                       | 5 EN 600x400         |
| PASSO TEGLIE                         | PAN CLEARANCE                       | 65 mm                |
| PESO NETTO                           | NET WEIGHT                          | 75 Kg                |
| PESO LORDO                           | GROSS WEIGHT                        | 100 Kg               |
| CAVO ELETTRICO                       | POWER CABLE                         | 16A EU PLUG          |
| ALIMENTAZIONE ELETTRICA              | POWER SUPPLY                        | 230 v - 1/50 Hz      |
| TUBO SCARICO ACQUA                   | DRAINAGE HOSE                       | Ø ½"                 |
| CONTROLLO CICLO: A TEMPO             | CYCLE CONTROL: TIMED                | Si                   |
| CONTROLLO CICLO: A SPILLONE          | CYCLE CONTROL: SENSOR PROBE         | Si                   |
| CORPO ESTERNO                        | EXTERIOR                            | AISI 304 finitura SB |
| INGOMBRO                             | ENCUMBRANCE                         | 0.6 m3               |

<sup>1</sup> Temp. evap. -10°C, temp. cond. +45°C / Evap. temp. -10°C, cond. temp. +45°C



DETTAGLIO A  
SCALA 1 : 6

