

TECHNICAL DATA SHEET

Order No. 486-1025

Item/Model SARO Wine cooling cabinet

model CV 800 PV

GTIN 4017337058365





- Material: (housing and interior) steel, plastic coated, black
- Climate class: 4
- 2 glass doors, lockable
- 4 adjustable grids for approx. 280 standard bottles
- LED-lighting
- Digital thermostat
- Forced air cooling
- Automatic defrost
- Temperature range: +5 / +20 °C
- Connection: 230 V 50 Hz 0.500 kW
- Grids: 4x W 1050 x D 413 mm
- Capacity: 765/585 liters
- External dimensions: W 1180 x D 645 x H 1980 mm
- Weight: 190 kg
- 4 castors, 2 with brakes
- Refrigerant: R290
- Energy efficiency class: C (spectrum A to G)

Origin Portugal customs tariff no. 84185019

Stand: 06.03.2025

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



SAFETY & WARNING INSTRUCTIONS

Order No. 486-1025

Item/Model SARO Wine cooling cabinet

model CV 800 PV

GTIN 4017337058365





Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- After transport or significant tilting, leave the device upright for at least 24 hours before turning it on to avoid damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unattended near it.
- Do not store flammable, explosive, or chemical substances in the device.
- Ventilation slots and openings must not be blocked to avoid overheating.
- Never immerse the device in water or clean it with a water jet; risk of short circuits and electric shock.
- In case of visible damage or malfunctions, immediately stop operation and contact the dealer.
- Do not place hot food or open liquids in the device to avoid condensation or freezing issues.
- Only use original spare parts and accessories that are approved for the device.
- Perform cleaning only when the device is switched off and disconnected from the power supply.
- The device is exclusively intended for storing and cooling food; other uses may cause damage and void the warranty.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- After a power failure or briefly disconnecting the power plug, wait at least 5 minutes before turning the device back on to avoid damage to the compressor.
- Be cautious when handling the door (glass). Do not lean or hit heavy objects against the door. If visible cracks or damage are present, do not use the door and have it replaced immediately by qualified personnel.
- Repairs and maintenance should only be carried out by qualified personnel.

Origin Portugal customs tariff no. 84185019

Stand: 06.03.2025

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY