

TECHNICAL DATA SHEET

Order No. 481-1000

Item/Model SARO Ice cream/freezer
model CUBE 35-2BD100A

GTIN 4017337063666



- Material: (housing + interior) steel, galvanized, white;
(sliding lid) insulated with high-quality aluminum frame
- 2-part sliding lid, with self-closing mechanism in the last part
- Chest freezer designed for packed ice cream (can also be used for other foods)
- Baskets (max. 3) can be ordered as an option
- Delivery ready to plug in (Schukoplug type F)
- Digital thermometer
- Manual temperature control (inside - already preset)
- Insulation: 77 mm (Polyurethane)
- Static cooling
- Manual defrost
- Suitable for ambient temperatures from +16 to +35 °C
- Temperature range: -16/ -23 °C
- Connection: 230 V / 1 Ph. / 50 Hz / 0.120 kW
- Volume (gross/net): 331 / 265 liters
- Internal dimensions: W 936 x D 536 x H 688 mm
- External dimensions: W 1094 x D 694 x H 867 mm
- 4 castors, lockable castors only available as an option
- Weight (net/gross): 53 / 57 kg
- Refrigerant: R290
- Energy efficiency class: D (spectrum A to G)
- Options:
 - * Lockable chest
 - * Different types of baskets
 - * Separation/sorting aids
 - * Glass attachments for direct sale

Origin Denmark

customs tariff no. 84181080

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 481-1000

Item/Model SARO Ice cream/freezer
model CUBE 35-2BD100A

GTIN 4017337063666



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block or cover ventilation slots and openings to ensure proper air circulation and prevent overheating.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Use only original spare parts and accessories approved for the device.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Always switch off the device and unplug it from the power supply before cleaning, maintenance, or extended periods of non-use.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.
- Do not place heavy objects on the device to avoid deformation or damage.
- Keep the power plug easily accessible to quickly disconnect the device from the power supply in case of emergency.

Origin Denmark

customs tariff no. 84181080

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827