

## TECHNICAL DATA SHEET

Order No. **323-1601**

Item/Model **SARO drawer cooling table with 2 drawers, model DRAW 3SK**

GTIN **4017337072248**



- **Material:** (housing, work surface, interior) stainless steel AISI 304, (Control panel) black lacquered steel
- **2 drawers with practical magnetic sealing**
- **Digital temperature control (DIXELL)**
- **Insulation: 50 mm**
- **Static cooling with fan**
- **Automatic defrosting and automatic evaporation of condensate**
- **Suitable for climate class 4, 5**
- **Temperature range: +1 / +4 °C**
- **Connection: 230 V / 1 Ph. / 50 Hz / 0.460 kW**
- **Capacity (gross/net): 265 / 166 L**
- **Internal dimensions (drawers): 2 x W 958 x D 545 mm**
- **Internal dimensions (unit): W 1000 x D 565 x H 470 mm**
- **External dimensions: W 1230 x D 700 x H 865 mm**
- **4 wheels, 2 lockable**
- **Weight (net/gross): 113 / 125 kg**
- **Refrigerant: R290**
- **Energy efficiency class: B (spectrum A+++ to G) with climate class 5**  
-> high-performance device!

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827

## SAFETY & WARNING INSTRUCTIONS

Order No.       **323-1601**

Item/Model      **SARO drawer cooling table with 2  
drawers,  
model DRAW 3SK**

GTIN             **4017337072248**



### Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin            China

customs tariff no.   84181020

Importer          Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827