

TECHNICAL DATA SHEET

Order No. **323-1471**

Item/Model SARO cooling table, 3 doors,

model KYLJA 3100 TN PRO

GTIN 4017337068067






- Material: (housing, work surface, interior) AISI 304 stainless steel
- 3 doors, self-closing, with practical magnetic seal
- 3 height-adjustable grids and support rail sets
- 3 bottom grids (390 x 505 mm) for optimal, energy-reducing air circulation
- Interior with rounded corners for easy cleaning
- Suitable for 1/1 GN-containers
- Pull-out compressor for easy cleaning
- Cleaning-free condenser
- Digital temperature control (DIXELL)
- Insulation: 60 mm
- Circulating air cooling with highly efficient fan
- Automatic fan shut-off system when door is opened
- Automatic defrosting and automatic evaporation of condensation
- Suitable for climate class 4, 5
- Temperature range: -2 / +8 °C
- Connection: 220 V / 1 Ph. / 50 Hz / 0,250 kW
- Grids for bottom: 3x W 390 x D 505 mm and grids: 3x W 335 x D 530 mm
- Volume (gross/net): 465 / 291 liters
- Internal dimensions: W 1234 x D 530 x H 564 mm
- External dimensions: W 1795 x D 700 x H 890-950 mm
- 6 height-adjustable feet, additional castors can be ordered as an option
- Weight (net/gross): 134 / 151 kg
- Refrigerant: R600a
- Energy efficiency class: A (spectrum A+++ to G) with climate class 5
- -> high-performance device!

Origin China customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry







SAFETY & WARNING INSTRUCTIONS

Order No. **323-1471**

Item/Model SARO cooling table, 3 doors,

model KYLJA 3100 TN PRO

GTIN **4017337068067**





Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY