

TECHNICAL DATA SHEET

Order No. **323-4530**

Item/Model **SARO Blast Chiller
model URSUS 10S**

GTIN **4017337071098**



- Material: (housing and interior) stainless steel, (Exterior Bottom) Galvanized steel
- Self-closing door
- Suitable for 10 x 1/1 GN, or W 600 x D 400 mm trays
- 4 preset temperature stages
- Core temperature sensor
- Manual defrost
- Rapid cooling: from +65 °C / + 10 °C in 85 minutes, highest load capacity per tray: 40 kg
- Shock freezing: from +65 °C / -18 °C in 183 minutes, highest load capacity: 28 kg
- Digital temperature control (DIXELL)
- Insulation: 70 mm
- Forced-air cooling
- 4 height adjustable feet: H 110 - 170 mm
- Connection: 230 V – 50 Hz – 0.900 kW
- Capacity (gross/net): 368 / 208 L
- interior dimensions: W 440 x D 695 x H 870 mm
- Exterior dimensions: W 800 x D 873 x H 1665 mm
- Weight (net/gross): 150 / 190 kg
- Refrigerant: R290

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-4530**

Item/Model **SARO Blast Chiller
model URSUS 10S**

GTIN **4017337071098**



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- Keep ventilation slots clear of obstructions to ensure optimal air circulation.
- After transport or tilting, allow the device to stand upright for at least 12 hours before switching it on to prevent damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store or use flammable, explosive, or chemical substances in or near the device.
- Never clean the device with a water jet or immerse it in liquids; risk of short circuits and electric shock.
- Always wear protective gloves when handling shock-frozen or chilled food to avoid cold burns.
- After a power outage or disconnection, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Do not place food with temperatures above 90°C in the device, as this can impair the cooling process.
- Regularly clean the condenser and evaporator. Wear protective gloves and a dust mask during cleaning to avoid injuries or inhaling dust.
- Ensure the device is disconnected from the power supply and the fan has come to a complete stop before cleaning to prevent electric shock and injury.
- The device is intended exclusively for commercial use for cooling and freezing food. Any other use may cause damage and compromise safety.
- Do not use damaged cables or plugs. Repairs and maintenance must only be performed by qualified personnel.
- Do not place heavy or liquid-filled objects on the device to avoid the risk of falling or electric shock.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- Do not operate the device outdoors or in damp areas, as this may lead to short circuits and hazards.
- Immediately stop operation if visible damage or malfunctions occur, and contact qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827