

TECHNICAL DATA SHEET

Order No. **323-10725**

Item/Model **SARO Cooling table with 2 doors and 2x
3 drawer set,
model KYLJA 4150 TN**

GTIN **4017337324576**



- **Material:** (housing and interior) stainless steel; (work surface) stainless steel
- **2 doors and 2x sets of 3 drawers, self-closing doors**
- **2 height-adjustable grids and 2 sets of support rails**
- **Digital temperature control (DIXELL)**
- **Insulation: 60 mm**
- **Forced air cooling**
- **Automatic defrost**
- **Temperature range: -2 / +8 °C**
- **Connection: 230 V - 50 Hz - 0.30 kW**
- **Grids: 2x W 335 x D 530 mm**
- **Capacity (gross/net): 616/273 liters**
- **External dimensions: W 2230 x D 700 x H 890-950 mm**
- **6 adjustable feet**
- **Weight: 213kg**
- **Refrigerant: R600a**
- **Energy efficiency class: C (spectrum A+++ to E)**
- **Sound level: approx. 40dB(A)**

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-10725**

Item/Model **SARO Cooling table with 2 doors and 2x
3 drawer set,
model KYLJA 4150 TN**

GTIN **4017337324576**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827