

TECHNICAL DATA SHEET

Order No. 323-15152

Item/Model SARO Pizza Worktable
model PZ9031 PRO

GTIN 4017337070985



- Material: (housing) stainless steel, (Countertop) Granite
- 3 doors, 6 uncooled drawers
- 3 adjustable shelves W 335 x D 530 mm + 3 shelf rail sets
- Bottom grate W 570 x D 323 mm, for better air circulation
- Automatic defrost and automatic evaporation of condensation water
- Digital temperature control (DIXELL)
- Insulation: 45 mm
- Cooling type: Circulated air cooling
- Suitable for climate class: 4
- Temperature range: +2 - +8 °C
- 4 feet, H 25-33 mm
- Connection: 230V / 50Hz / 0.110 kW
- Capacity (gross/net): 400 / 252 L
- Interior dimensions: W 1275 x D 585 x H 454 mm
- Exterior dimensions: W 1885 x D 700 x H 1020 mm
- Weight (net/gross): 325 / 340 kg
- Refrigerant: R600a
- Energy efficiency class: A (spectrum A+++ to E)

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-15152

Item/Model SARO Pizza Worktable
model PZ9031 PRO

GTIN 4017337070985



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827