

TECHNICAL DATA SHEET

Order No. 323-1020

Item/Model SARO Commercial refrigerator - 2/1 GN
model TORE GN 700 TN

GTIN 4017337323043



- Material: (housing and interior) stainless steel
- Door self-closing, lockable
- Interchangeable door stop
- 3 height-adjustable grids (2/1 GN)
- Digital temperature control (DIXELL)
- Insulation: 65 mm
- Forced air cooling
- Automatic defrost
- Temperature range: -2 / +8 °C
- Connection: 230 V - 50 Hz - 0.350 kW
- Grids: 3x W 540 x D 630 mm
- Capacity (gross/net): 685/422 liters
- Internal dimensions: W 604 x D 680 x H 1397 mm
- External dimensions: W 740 x D 830 x H 2010 mm
- Weight: 140 kg
- Refrigerant: R600a
- Energy efficiency class: E (spectrum A+++ to E)

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-1020

Item/Model SARO Commercial refrigerator - 2/1 GN
model TORE GN 700 TN

GTIN 4017337323043



Safety and Warning Instructions

- The device must only be connected to a properly installed outlet that is grounded and matches the specifications on the rating plate.
- The refrigerant is flammable; avoid damage to the cooling circuit. In case of a leak, ventilate the room well and avoid open flames.
- Children and unauthorized persons must not operate the device or be left unattended near it while it is in operation.
- Never clean the device with a water jet or high-pressure cleaner; risk of electric shock.
- Ventilation slots must remain free of obstructions to ensure optimal air circulation and avoid overheating.
- The cable must not be routed over sharp edges or hot surfaces, and should be regularly checked for damage. If damaged, do not use the device.
- After transport or tilting of the device, leave it standing for at least 5 hours before switching it on to avoid damage to the refrigerant circuit.
- The device should not be placed near heat sources such as radiators or ovens. Avoid direct sunlight and strong drafts.
- Do not place hot food or open containers of liquid in the cooling device to prevent condensation issues and inefficient cooling.
- Always switch off the device and unplug it before cleaning or performing maintenance.
- Do not make any modifications or alterations to the device; repairs must only be carried out by qualified personnel.
- Use the device only for its intended purpose, such as the storage of food. Using it for other purposes may cause damage and void the warranty.
- The device must not be used for storing medications, chemicals, or flammable substances.
- In case of malfunctions or faults, immediately stop operation and contact a qualified dealer.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827