

TECHNICAL DATA SHEET

Order No. **323-1410**

Item/Model **SARO Freezer
model GN 700 BT PRO**

GTIN **4017337068012**



- **Material:** (housing and interior) stainless steel
- **Shelves:** 3 shelves W 530 x H 650 mm, adjustable in height, 1 bottom shelf W 510 x D 605 mm
- **Self-closing door, lockable; reversible door hinges**
- **Embossed side walls for easy cleaning, 15 levels**
- **High-efficiency compressor, for energy saving**
- **Rounded edges inside, for easy cleaning**
- **Digital temperature control (DIXELL)**
- **Insulation: 100 mm**
- **Forced air cooling**
- **Automatic defrosting**
- **Suitable for climate class: to 5**
- **Temperature range: -18 / -22 °C**
- **4 height adjustable feet: H 110-170 mm**
- **Connection: 220 V - 50 Hz - 0.250 kW**
- **Capacity (gross/net): 560 / 408 L**
- **Internal dimensions: W 533 x D 700 x H 1501 mm**
- **External dimensions: W 740 x D 875 x H 2090 mm**
- **Weight (net/gross): 125 / 145 kg**
- **Refrigerant R290**
- **Energy efficiency class: B (Range from A+++ to G) with climate class 5**
-> high-performance device!

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-1410**

Item/Model **SARO Freezer**
model GN 700 BT PRO

GTIN **4017337068012**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827