

## TECHNICAL DATA SHEET

Order No. 486-2520

Item/Model SARO Refrigerator  
model ARV 430 CS A PO

GTIN 4017337067411



- Material: (housing) stainless steel; (interior) plastic, white
- 1 door, self-closing, lockable
- Door stop changeable
- 4 height-adjustable, plastic-coated grids
- Digital temperature control
- Water-based polyurethane insulation, 50 mm
- Static cooling with circulating air fan
- Automatic defrost
- Suitable for climate class 4
- Temperature range +1 / +8 °C
- Connection: 230 V - 50 Hz - 0.180 kW
- Grids: 4x W 495 x D 428 mm
- Volume (gross/net): 386 / 308 liters
- Internal dimensions: W 477 x D 470 x H 1590 mm
- External dimensions: W 590 x D 600/645 x H 1860 mm
- 4 wheels + 2 adjustable feet (H 25 mm)
- Weight (net/gross): 76 / 87 kg
- Refrigerant: R600a
- Energy efficiency class: D (spectrum A+++ to E)

Origin Portugal

customs tariff no. 84181020

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827

## SAFETY & WARNING INSTRUCTIONS

Order No. 486-2520

Item/Model SARO Refrigerator  
model ARV 430 CS A PO

GTIN 4017337067411



### Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- **The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.**
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin Portugal

customs tariff no. 84181020

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827