

TECHNICAL DATA SHEET

Order No. 323-1010

Item/Model SARO Ventilated Freezer - 2/1 GN
Container
model KYRA GN 700 BT

GTIN 4017337323029



- Material: (housing and interior) stainless steel
- Door self-closing, lockable
- Door stop changeable
- 3 height-adjustable grids (2/1 GN)
- Digital temperature control (DIXELL)
- Insulation: 65 mm
- Forced air cooling
- Automatic defrost
- Temp. -18 / -22 °C
- Connection: 230 V - 50 Hz - 0.750 kW
- Grids: 3x W 540 x D 630 mm
- Capacity (gross/net): 685/427 liters
- Internal dimensions: W 604 x D 680 x H 1397 mm
- External dimensions: W 740 x D 830 x H 2010 mm
- Weight: 173kg
- Refrigerant: R290
- Energy efficiency class: D (spectrum A+++ to E)
- Sound level: approx. 48dB(A)

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 323-1010

Item/Model SARO Ventilated Freezer - 2/1 GN
Container
model KYRA GN 700 BT

GTIN 4017337323029



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- **The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.**
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827