

TECHNICAL DATA SHEET


Order No. 323-2212

Item/Model SARO Refrigerator

model HK 200 PRO

GTIN 4017337070992





- Lockable door
- Reversible door hinge
- Newly designed air circulation provides better airflow for more uniform temperature
- Automatic fan shutdown system to reduce cold loss and energy consumption
- 3 adjustable shelves, 2 x W 502 x D 440 mm + 1 x W 502 x D 211 mm
- Digital temperature control (DIXELL)
- Static cooling with circulation fan
- Automatic defrost
- Temperature range: -2 / +8 °C
- Connection: 230 V 50 Hz 0.07 kW
- Capacity (gross/netto): 129 / 66 liters
- Internal dimensions: W 510 x D 485 x H 620 mm
- External dimensions: W 600 x D 615 x H 855 mm
- Weight (net/gross): 49 / 54 kg
- Refrigerant: R600a
- Energy efficiency class: A+ (spectrum A+++ to E)

Origin China customs tariff no. 84181080

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



SAFETY & WARNING INSTRUCTIONS

Order No. 323-2212

Item/Model SARO Refrigerator

model HK 200 PRO

GTIN 4017337070992





Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- After transport or significant tilting, leave the device upright for at least 24 hours before turning it on to avoid damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unattended near the device.
- Do not store flammable, explosive, or chemical substances in the device.
- Ventilation slots and openings must not be blocked to prevent overheating.
- Never immerse the device in water or clean it with a water jet; risk of short circuits and electric shock.
- If visible damage or malfunctions occur, immediately stop operation and contact the dealer.
- Do not place hot food or open liquids in the device to avoid condensation or freezing issues.
- Only use original spare parts and accessories that are approved for the device.
- Clean only when the device is switched off and unplugged.
- The device is exclusively intended for storing and cooling food; other uses may cause damage and void the warranty.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- After a power failure or briefly disconnecting the power cord, wait at least 5 minutes before turning the device back on to avoid damage to the compressor.
- Repairs and maintenance should only be carried out by qualified personnel.

Origin China customs tariff no. 84181080

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY