

TECHNICAL DATA SHEET

Order No. 330-3220

Item/Model SARO Cooled Countertop Front + Rear
Sliding Doors
model SELF 165K

GTIN 4017337068951



- Material: (housing) stainless steel, (sides, viewing window) tempered glass, (door frame) plastic
- Double glazed on all four sides
- 2 adjustable chrome-plated shelves,
1x W 813 x D 335 mm, 1x W 813 x D 367 mm
- LED-interior-lighting on top
- Digital temperature control
- Sliding doors at the front and back
- Fan cooling system
- Automatic defrost
- Suitable for climate class: 4
- Temperature range: 0 / +12 °C
- Connection: 230 V - 50 Hz - 0.210 kW
- Capacity (gross/net): 160 / 106 liters
- Internal dimensions: W 840 x D 480 x H 410 mm
- External dimensions: W 880 x D 568 x H 686 mm
- Weight (net/gross): 66 / 69.5 kg
- Refrigerant: R600a
- Energy efficiency class: B (spectrum A to G)

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 330-3220

Item/Model SARO Cooled Countertop Front + Rear
Sliding Doors
model SELF 165K

GTIN 4017337068951



Safety and Warning Instructions

- Only place the device on a stable, level, and non-slip surface.
- Ensure the mains voltage matches the specifications on the rating plate.
- All packaging materials and protective films must be completely removed before first use.
- After transport, let the device stand upright for at least 12 hours before switching it on to prevent damage to the refrigerant circuit.
- Ensure the ventilation slots are not blocked to maintain optimal air circulation and cooling.
- Do not place the device near heat sources or in direct sunlight.
- Bottles with high alcohol content must be tightly sealed and stored upright in the device.
- Do not use electrical devices or heating sources inside the appliance.
- Never clean the device with a water jet or high-pressure cleaner to avoid the risk of electric shock and short circuits.
- Do not use damaged cables or plugs. Replacement must only be carried out by qualified personnel.
- Always switch off the device and disconnect it from the power supply before cleaning, maintenance, or repairs.
- Clean the door seal with water only and ensure it remains intact to prevent energy loss.
- The refrigerant is flammable; if the cooling circuit is damaged, ventilate the room well and avoid open flames.
- Children must not use the device unsupervised or play near it.
- The device is intended solely for the storage of food; any other use may cause damage and void the warranty.
- Regular cleaning of the condenser by qualified personnel is recommended to extend the device's lifespan.
- Handle the display case with care (fragile glass). Do not lean heavy objects against it or strike it.
- If visible damage or malfunctions occur, immediately stop operation and contact qualified personnel.

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827