

## **TECHNICAL DATA SHEET**

Order No. **323-3110** 

Item/Model SARO Refrigerated undertable

model UGN 2100 TN

GTIN **4017337045778** 





- Material: (housing and interior) stainless steel; (work surface) stainless steel
- 2 doors, self-closing
- 2 height-adjustable grids and 2 sets of support rails
- Suitable for 1/1 GN-containers
- Extractable compressor for easy cleaning
- Digital temperature control (DIXELL)
- Insulation: 60 mm
- Forced air cooling
- Automatic defrost
- Temperature range: -2 / +8 °C
- Connection: 230 V 50 Hz 0.350 kW
- Grids: 2x W 328 x D 530 mm
- Capacity (gross/net): 214 / 108 liters
- Internal dimensions: W 795 x D 580 x H 340 mm - External dimensions: W 1360 x D 700 x H 650 mm
- 4 adjustable feetWeight: 152kg
- Refrigerant: R600a
- Energy efficiency class: B (spectrum A+++ to G) with climate class 5
- -> high-performance device!
- Sound level: approx. 40dB(A)

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Subject to technical changes and errors. Designs and illustrations may differ from the original.





## **SAFETY & WARNING INSTRUCTIONS**

Order No. **323-3110** 

Item/Model SARO Refrigerated undertable

model UGN 2100 TN

GTIN 4017337045778





## **Safety and Warning Instructions**

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY