

TECHNICAL DATA SHEET

Order No. **323-1003**

Item/Model **SARO Saladette with 3 doors,
model BALDUR S 903**

GTIN **4017337323258**



- Material: (housing and interior) stainless steel
- 3 doors, self-closing, telescopic sliding lid
- Polyethylene cutting board
- Delivery without GN container
- Allocation option above: 4x 1/1 GN-containers, up to 150 mm deep (other combinations possible)
- 3 height-adjustable grids and 3 sets of support rails
- Digital temperature control (DIXELL)
- Evaporator foamed on 3 sides
- Static cooling with circulating air fan
- Automatic defrost
- Temperature range: +2 / +8 °C
- Connection: 230 V - 50 Hz - 0.230 kW
- Grids: 3x W 323 x D 570 mm
- External dimensions: W 1365 x D 700 x H 870-890 mm
- Weight: 120.5 kg
- Refrigerant: R600a
- Energy consumption: approx. 3.725 kWh/24h (lid closed)

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-1003**

Item/Model **SARO Saladette with 3 doors,
model BALDUR S 903**

GTIN **4017337323258**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827