

TECHNICAL DATA SHEET

Order No. 323-4220

Item/Model SARO Bar Cooler 4 door

model BC 4100

GTIN 4017337062706





- 4 doors, self-closing, door stop cannot be changed

- 8 adjustable grids

- Height adjustable feet

- Digital temperature control (DIXELL)

- Insulation: 40 mm

- Forced air cooling

- Automatic defrost

- Temperature range: +2 / +8 °C

- Connection: 230 V - 50 Hz - 0,320 kW

- Grids: 8x W 430 x D 395 mm

- Capacity (gross/net): 598 / 484 liters

Internal dimensions: W 2162 x D 415 x H 720 mm
External dimensions: W 2542 x D 513 x H 860 mm

Weight: 123kgRefrigerant: R600a

- Energy efficiency class: C (spectrum A+++ to E)

Origin China customs tariff no. 84185019

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



SAFETY & WARNING INSTRUCTIONS

Order No. 323-4220

Item/Model SARO Bar Cooler 4 door

model BC 4100

GTIN 4017337062706





Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block ventilation slots and openings to avoid overheating and inefficient cooling.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Always switch off the device, unplug it, and allow it to cool completely before cleaning or maintenance.
- Open doors and drawers only as long as necessary to minimize energy loss.
- Use only original spare parts and accessories approved for the device.
- Do not place hot food or uncovered liquids inside the device to prevent condensation or icing problems.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.

Origin China customs tariff no. 84185019

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY