

TECHNICAL DATA SHEET

Order No. **453-1124**

Item/Model **SARO Freezer with glass doors -
model GTK 930 PRO**

GTIN **4017337067275**



- **Material:** (housing) steel with black powder coating; (interior, glass door frame, front panel) Black-painted aluminum; (Door handle) Aluminum
- **2 self-closing doors, triple-glazed, with heated film to prevent fogging**
- **10 height-adjustable shelves with price strips**
- **2x LED-interior-lighting (vertical), separately switchable**
- **Digital temperature control**
- **Insulation: 60 mm**
- **Forced air cooling**
- **Automatic defrost**
- **Temperature range: -15 / -18 °C**
- **Power supply: 230 V - 50 Hz - 1.205 kW**
- **Shelves (reinforced wire mesh): 10x W 551 x D 470 mm**
- **Capacity (gross/net): 1006/702 liters**
- **interior dimensions: W 1133 x D 580 x H 1538 mm**
- **Exterior dimensions: W 1253 x D 760 x H 2003 mm**
- **4 wheels**
- **Weight (net/gross): 240 / 270 kg**
- **Refrigerant: R290, dual refrigeration circuit**
- **Energy efficiency class: D (spectrum A to G)**

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry

ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **453-1124**

Item/Model **SARO Freezer with glass doors -
model GTK 930 PRO**

GTIN **4017337067275**



Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- After transport or significant tilting, leave the device upright for at least 24 hours before turning it on to avoid damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unattended near it.
- Do not store flammable, explosive, or chemical substances in the device.
- Ventilation slots and openings must not be blocked to avoid overheating.
- Never immerse the device in water or clean it with a water jet; risk of short circuits and electric shock.
- In case of visible damage or malfunctions, immediately stop operation and contact the dealer.
- Do not place hot food or open liquids in the device to avoid condensation or freezing issues.
- Only use original spare parts and accessories that are approved for the device.
- Perform cleaning only when the device is switched off and disconnected from the power supply.
- The device is exclusively intended for storing and cooling food; other uses may cause damage and void the warranty.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- After a power failure or briefly disconnecting the power plug, wait at least 5 minutes before turning the device back on to avoid damage to the compressor.
- Be cautious when handling the door (glass). Do not lean or hit heavy objects against the door. If visible cracks or damage are present, do not use the door and have it replaced immediately by qualified personnel.
- Repairs and maintenance should only be carried out by qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827