

## **TECHNICAL DATA SHEET**

Order No. **323-1172** 

Item/Model SARO Cooling table with 4 doors and

backsplash,

model KYLJA 4200 TN

GTIN **4017337057740** 






- Material: (housing and interior) stainless steel; (work surface) stainless steel
- Upstand: height 100 mm
- 4 doors, self-closing
- 4 height-adjustable grids and 4 sets of support rails
- Extractable compressor for easy cleaning
- Do-it-yourself drawers available separately (see page 69)
- Digital temperature control (DIXELL)
- Insulation: 60 mm
- Forced air cooling
- Automatic defrost
- Temperature range: -2 / +8 °C
- Connection: 230 V 50 Hz 0.35 kW
- Grids: 4x W 335 x D 530 mm
- Capacity (gross/net): 616/393 liters
- External dimensions: W 2230 x D 700 x H 890-950 mm (+100 stickers)
- 6 adjustable feet- Weight: 193kg
- Refrigerant: R600a
- Energy efficiency class: C (spectrum A+++ to G) with climate class 5
- -> high-performance device!

Origin China customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry



Stand: 30.07.2025



## **SAFETY & WARNING INSTRUCTIONS**

Order No. **323-1172** 

Item/Model SARO Cooling table with 4 doors and

backsplash,

model KYLJA 4200 TN

GTIN 4017337057740





## **Safety and Warning Instructions**

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY