



MOD : DRK12-CB

Production code : 30000033952

06/2025

Technical data sheet



DRK12-CB

CHARACTERISTICS

Climate class		: CC1 TO EN22044
Temperature range	(°C)	: 1/+9C
Power	(W)	: 4,3 A / 730 W
Voltage/freq.	(V / Hz.)	: 220-240V/50Hz

TECHNICAL SPECIFICATIONS

External dimensions	(WXDXH)mm	: 1200 X 835 X 2001
Internal dimensions	(WXDXH)mm	: 1125 X 641 X 1386
Package dimensions	(WXDXH)mm	: 1230 X 870 X 2139
Gross volume	(L)	: 1230
Net volume	(L)	: 1083
Gross weight	(kg)	: 212
Net weight	(kg)	: 198
Outer body		: 0.6 mm.DKP / sheet steel
Inner liner		: 0.45 mm. Boyalı Sac / Prepainted Sheet
Insulation material		: Sert P.U. / Rigid P.U.
Insulation density		: 38~40 kg/m ³
Internal light		: Yes
Canopy light		: Yes
Light Switch		: Yes
Door Switch		: NO
Levelling leg (front)		: 2 Adet / 2 Pcs.
Levelling leg (back)		: -
Castor		: 4 Adet / 4 Pcs.
Comp. capacity		: CUBIGEL , 2065 W
Evaporator		: Fin CU evap
Evap. ventilator		: FAN AKSIYEL 5/33W - 200/28 PROPELLER
Condenser		: WOT condenser
Cond. ventilator		: FAN AKSIYEL 7/38W - 250/28 PROPELLER
Thermostat		: MEKANİK
Refrigerant		: R290
Refrigerant charge	(g)	: 122 GR
Approvals		: CE

* E ternal depth is without back stopper.

