

TECHNICAL DATA SHEET

Order No. 323-4410

Item/Model SARO Refrigerator

model HK 600I S/S

GTIN 4017337071760





- Material: (housing and interior) stainless steel
- 3 shelves: W 654 x D 525 mm, adjustable in height, 1 bottom shelf: W 654 x D 330 mm
- Lockable, reversible door hinge
- Digital temperature control (DIXELL)
- Insulation: 60mm
- Cooling type: Static cooling with circulating fan
- Automatic defrosting
- Suitable for climate class: 4
- Temperature range: 0 / +8 °C
- 2 feet + 2 castors
- Connection: 220V / 50Hz / 0.12 kW
- Capacity (gross/net): 620 / 442 L
- Internal dimensions: W 657 x D 580 x H 1660 mm
- External dimensions: W 777 x D 745 x H 1895 mm
- Weight (net/gross): 90 / 97 kg
- Refrigerant R600a
- Energy efficiency class: A (spectrum from A+++ to E)

Origin China customs tariff no. 84181020

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



SAFETY & WARNING INSTRUCTIONS

Order No. 323-4410

Item/Model SARO Refrigerator

model HK 600I S/S

GTIN 4017337071760





Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- After transport or significant tilting, leave the device upright for at least 24 hours before turning it on to avoid damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unattended near the device.
- Do not store flammable, explosive, or chemical substances in the device.
- Ventilation slots and openings must not be blocked to prevent overheating.
- Never immerse the device in water or clean it with a water jet; risk of short circuits and electric shock.
- If visible damage or malfunctions occur, immediately stop operation and contact the dealer.
- Do not place hot food or open liquids in the device to avoid condensation or freezing issues.
- Only use original spare parts and accessories that are approved for the device.
- Clean only when the device is switched off and unplugged.
- The device is exclusively intended for storing and cooling food; other uses may cause damage and void the warranty.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- After a power failure or briefly disconnecting the power cord, wait at least 5 minutes before turning the device back on to avoid damage to the compressor.
- Repairs and maintenance should only be carried out by qualified personnel.

Origin China customs tariff no. 84181020

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY