

TECHNICAL DATA SHEET

Order No. **323-1434**

Item/Model **SARO Pizza Worktable
model PZ2600TN PRO**

GTIN **4017337070947**



- **Material: (housing) stainless steel, (worktop) granite**
- **2 Bottom grates W 465 x D 605 mm, for better air circulation**
- **2 self-closing doors, 15 cm backsplash**
- **Circulating cooling with high-efficiency fan and optimal air flow**
- **Digital temperature control (DIXELL)**
- **Insulation: 60mm**
- **Automatic defrost**
- **Suitable for climate class: 4, 5**
- **Temperature range: +2 / +8 °C**
- **4 feet, H 180-240 mm**
- **Connection: 220V - 50Hz - 0.3 kW**
- **Capacity (gross/net): 428 / 268 L**
- **interior dimensions: W 945 x D 680 x H 560 mm**
- **Exterior dimensions: W 1510 x D 800 x H 1090 mm**
- **Weight (net/gross): 257 / 275 kg**
- **Refrigerant: R600a**
- **Energy efficiency class: A (spectrum A+++ to G) with climate class 5**
- **-> high-performance device!**

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-1434**

Item/Model **SARO Pizza Worktable
model PZ2600TN PRO**

GTIN **4017337070947**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827