

TECHNICAL DATA SHEET

Order No. 323-3152

Item/Model SARO Ventilated cooling table

model GN 3100 TNG

GTIN 4017337037056





- 3 glass doors, self-closing, double glazing

- Suitable for 1/1 GN-containers

- 3 height-adjustable grids and 3 sets of support rails

- Extractable compressor for easy cleaning

- Digital temperature control (DIXELL)

- Insulation: 60 mm

- Forced air cooling

- Automatic defrost

- Temperature range: +2 / +8 °C

- Connection: 230 V - 50 Hz - 0.350 kW

- Grids: 3x W 328 x D 530 mm - Volume (gross): 464 liters

- Internal dimensions: W 1234 x D 580 x H 596 mm

- External dimensions: W 1795 x D 700 x H 890-950 mm

4 adjustable feetWeight: 190kgRefrigerant: R600a

- Energy efficiency class: C (spectrum A to G)

- Sound level: approx. 40dB(A)



Origin China customs tariff no. 84185090

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY



SAFETY & WARNING INSTRUCTIONS

Order No. 323-3152

Item/Model SARO Ventilated cooling table

model GN 3100 TNG

GTIN 4017337037056





Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- After transport or significant tilting, leave the device upright for at least 24 hours before turning it on to avoid damage to the cooling circuit.
- Children and unauthorized persons must not operate the device or be left unattended near it.
- Do not store flammable, explosive, or chemical substances in the device.
- Ventilation slots and openings must not be blocked to avoid overheating.
- Never immerse the device in water or clean it with a water jet; risk of short circuits and electric shock.
- In case of visible damage or malfunctions, immediately stop operation and contact the dealer.
- Do not place hot food or open liquids in the device to avoid condensation or freezing issues.
- Only use original spare parts and accessories that are approved for the device.
- Perform cleaning only when the device is switched off and disconnected from the power supply.
- The device is exclusively intended for storing and cooling food; other uses may cause damage and void the warranty.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- After a power failure or briefly disconnecting the power plug, wait at least 5 minutes before turning the device back on to avoid damage to the compressor.
- Be cautious when handling the door (glass). Do not lean or hit heavy objects against the door. If visible cracks or damage are present, do not use the door and have it replaced immediately by qualified personnel.
- Repairs and maintenance should only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 06.03.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY