

TECHNICAL DATA SHEET

Order No. **323-1820**

Item/Model SARO cooling table with 2 doors and

upstand,

model SNACK 2200 TN

GTIN 4017337068142





- Material: (housing and interior) stainless steel; (worktop) stainless steel, with upstand (100 mm)
- 2 doors, self-closing, with convenient magnetic sealing
- 2 adjustable shelves and support rail sets
- Pull-out compressor for easy cleaning
- Digital temperature control (DIXELL)
- Insulation: 60 mm
- Circulating cooling
- Automatic defrost
- Suitable for climate class 4, 5
- Temperature range: -2 / +8 °C
- Connection: 230 V 50 Hz 0.300 kW
- Shelves: 2x W 335 x D 430 mm
- Capacity (gross/net): 260 / 155 liters
- interior dimensions: W 799 x D 430 x H 564 mm
- Exterior dimensions: W 1360 x D 600 x H 890-950/1050 mm
- 4 adjustable feet
- Weight (net/gross): 97 / 119 kg
- Refrigerant: R600a
- Energy efficiency class: B (spectrum A+++ to G)
 with climate class 5 -> High-performance device!

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Subject to technical changes and errors.



SAFETY & WARNING INSTRUCTIONS

Order No. **323-1820**

Item/Model SARO cooling table with 2 doors and

upstand,

model SNACK 2200 TN

GTIN 4017337068142





Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY