

TECHNICAL DATA SHEET

Order No. 481-1060

Item/Model SARO commercial chest freezer with
insulated hinged lid,
model EL 45

GTIN 4017337065295



- Material: (housing + interior) steel, powder-coated, white;
(hinged lid) plastic, white, foamed inside
- Hinged lid insulated, lockable
- Chest freezer designed for packed ice cream (can also be used for other foods)
- 2 mesh baskets for hanging included (3 possible)
- Delivery ready to plug in (Schukoplug type F)
- Optional chest with wheels and/or digital, integrated thermometer available
- Manual temperature control (outside, front)
- Insulation: 60 mm
- Static cooling
- Manual defrost
- Suitable for ambient temperatures from +16 to +30 °C
- Temperature range: -16/ -22 °C
- Connection: 230 V - 50 Hz - 0.146 kW
- Volume (gross/net): 416 / 361 liters
- Internal dimensions: W 1186 x D 536 x H 697 mm
- External dimensions: W 1305 x D 655 x H 865 mm
- 4 feet, levelable
- Weight (net/gross): 64 / 68 kg
- Refrigerant: R600a
- Energy efficiency class: C (spectrum A to G)
- More options:
 - * different types of baskets
 - * Separation/sorting aids

Origin Denmark

customs tariff no. 84181080

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 481-1060

Item/Model SARO commercial chest freezer with insulated hinged lid, model EL 45

GTIN 4017337065295



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block or cover ventilation slots and openings to ensure proper air circulation and prevent overheating.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Use only original spare parts and accessories approved for the device.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Always switch off the device and unplug it from the power supply before cleaning, maintenance, or extended periods of non-use.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.
- Do not place heavy objects on the device to avoid deformation or damage.
- Keep the power plug easily accessible to quickly disconnect the device from the power supply in case of emergency.

Origin Denmark

customs tariff no. 84181080

Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827