

TECHNICAL DATA SHEET

Order No. 437-1040

Item/Model SARO Bar cooler with sliding doors
model BC 320 SD

GTIN 4017337047703



- Material: (housing) enamelled steel, black; (interior) aluminum
- 3 sliding doors, double glazing
- 6 height-adjustable chrome grilles
- LED-interior-lighting, separately switchable
- Height adjustable legs
- Digital temperature control (DIXELL)
- Forced air cooling
- Automatic defrost
- Temperature range: +2 / +10 °C
- Connection: 230 V - 50 Hz - 0.270 kW
- Grids: 6x W 440 x D 346 mm
- Capacity: 320 liters
- External dimensions: W 1350 x D 520 x H 850 mm
- Weight: 90 kg
- Refrigerant: R600a
- Energy efficiency class: E (spectrum A to G)

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 437-1040

Item/Model SARO Bar cooler with sliding doors
model BC 320 SD

GTIN 4017337047703



Safety and Warning Instructions

- Place the device exclusively on a stable, level, and non-slip surface.
- Before connecting, ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate the device or remain unsupervised nearby.
- After transportation or tilting, the device must not be operated for 24 hours to allow the refrigerant to settle in the compressor.
- **During operation, the ventilation openings and compressor can become hot—risk of burns. Avoid touching.**
- Do not store or use flammable, explosive, or chemical substances inside or near the device.
- Never immerse the device in water or clean it with a water jet; there is a risk of short circuits and electric shock.
- Before cleaning or maintenance, always switch off the device, disconnect it from the power supply, and allow it to cool completely.
- If visible damage or malfunctions occur, immediately stop operation and contact qualified personnel.
- Handle the glass door with care; it is fragile. Do not lean objects against or strike the glass door.
- Keep ventilation slots free from obstructions to prevent the device from overheating.
- The refrigerant is flammable; in case of a leak, ventilate the room well and avoid open flames.
- Do not place heavy or liquid-filled items on the device to prevent damage and liquid ingress.
- Do not operate the device near heat sources or direct sunlight to avoid compromising its cooling performance.
- **If condensation appears on the exterior, wipe it off with a dry cloth—this is normal in warm or humid climates.**
- Repairs and maintenance must only be performed by qualified personnel using original spare parts.
- Dispose of packaging materials such as plastic wrap and styrofoam safely, as they can pose a suffocation hazard to children.
- Keep doors open only as long as necessary to avoid energy loss.
- The device is intended exclusively for storing and cooling beverages and food; any other use may cause damage and void the warranty.

Origin China

customs tariff no. 84185019

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827