

## **TECHNICAL DATA SHEET**

Order No. **323-1436** 

Item/Model SARO Pizza Worktable

model PZ3600TN PRO

GTIN 4017337070954







- 3 bottom grates W 465 x D 605 mm, for better air circulation

- 3 self-closing doors, 15 cm backsplash

- Recirculating air cooling with a highly efficient fan and optimal air circulation

- Digital temperature control (DIXELL)

- Insulation: 60mm

- Automatic defrosting

- Suitable for climate class: 4, 5

- Temperature range: +2 / +8 °C

- 6 legs, H 180-240 mm

Connection: 220V - 50Hz - 0.3 kW
Capacity (gross/net): 635 / 410 L

- Internal dimensions: W 1455 x D 660 x H 569 mm

- External dimensions: W 2020 x D 800 x H 1030-1090 mm

- Weight (net/gross): 320 / 340 kg

- Refrigerant: R600a

- Energy efficiency class: A (scale A+++ to G) met klimaatklasse 5

-> high-performance device!

Origin China customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827





## **SAFETY & WARNING INSTRUCTIONS**

Order No. 323-1436

Item/Model SARO Pizza Worktable

model PZ3600TN PRO

GTIN 4017337070954





## **Safety and Warning Instructions**

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China customs tariff no. 84185090

Stand: 30.07.2025

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY