

## TECHNICAL DATA SHEET

Order No. **446-1010**

Item/Model **SARO Wine cooling cabinet, 2 zones,  
model WK 77D**

GTIN **4017337047611**



- **Material: (housing) steel powder coated, black; (interior) plastic, black**
- **Glass door, lockable**
- **Door with Low-E glass for less energy loss**
- **With inverter compressor, performance is based on required refrigeration demand**
- **Digital Control**
- **Insulation: 50 mm**
- **2 climate zones, setting of only one zone also possible**
- **8 wooden grids for approx. 77 standard bottles**
- **LED-lighting (white), separately switchable**
- **Double forced air cooling**
- **Automatic defrost**
- **Temperature zone 1: +5 / +12 °C; Zone 2: +12 / +20 °C**
- **Connection: 230 V - 50 Hz - 0.160 kW**
- **Capacity: 191 liters**
- **External dimensions: W 500 x D 595 x H 1280 mm**
- **Weight: 52kg**
- **Refrigerant: R600a**
- **Energy efficiency class: G (spectrum A to G)**

Origin China  
customs tariff no. 84181020  
Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827

## SAFETY & WARNING INSTRUCTIONS

Order No. **446-1010**

Item/Model **SARO Wine cooling cabinet, 2 zones,  
model WK 77D**

GTIN **4017337047611**



### Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure the mains voltage matches the specifications on the nameplate.
- Children and unauthorized persons must not operate or be unsupervised near the device.
- Immediately discontinue use if visible damage or malfunctions occur, and contact qualified personnel.
- Do not place the device near heat sources or in direct sunlight, as this may affect efficiency.
- Keep ventilation openings clean and unobstructed to avoid overheating.
- Never clean the device with a water jet or immerse it in liquids to prevent short circuits and electric shock.
- The refrigerant is flammable. Avoid damaging the cooling circuit to minimize the risk of leaks.
- After transporting the device, let it stand still for 24 hours before connecting it to the power supply to allow the refrigerant to settle.
- The device is intended exclusively for wine storage. Do not store flammable, explosive, or unsuitable substances in it.
- Repairs must only be performed by qualified personnel using original spare parts.
- Dispose of packaging materials safely and keep them out of the reach of children to prevent choking hazards.
- Do not turn on the device if it has become wet. Have it inspected by a professional before the next use.
- Operating the device in very humid or poorly ventilated areas may impair functionality and cause damage.
- Regularly inspect the power cord for damage and have it replaced by qualified personnel if necessary.
- Do not make changes to the temperature switches or ventilation openings during operation to ensure proper functionality.
- Unplug the device and ensure all moving parts have stopped before cleaning or maintenance.
- When loading and unloading, ensure no objects block the ventilation openings or the fan.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827