

## TECHNICAL DATA SHEET

Order No. 465-1085

Item/Model SARO Saladette with glass top  
model ES 900 G

GTIN 4017337050871



- Material: (housing and interior) stainless steel; (top) glass
- 2 doors, self-closing
- Polyethylene cutting board
- Glass attachment with 2 shelves
- Delivery without GN container
- Allocation option above: 10x 1/4 GN or 2x 1/1 GN and 3x 1/6 GN-containers
- 2 height-adjustable grids and 2 sets of support rails
- Digital temperature control (Dixell)
- Evaporator foamed on 3 sides
- Static cooling with circulating air fan
- Automatic defrost
- Suitable for ambient temperatures from approx. 16 to 38 °C
- Temperature range: +2 / +8 °C
- Connection: 230 V - 50 Hz - 0.175 kW
- Grids: 2x W 323 x D 560 mm
- Capacity (gross/net) 240/198 liters
- External dimensions: W 903 x D 700 x H 856/1289 mm
- Weight: 92kg
- Refrigerant: R600a
- Energy consumption: approx. 2.2 kWh/24h (all container lids closed)

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827

## SAFETY & WARNING INSTRUCTIONS

Order No. 465-1085

Item/Model SARO Saladette with glass top  
model ES 900 G

GTIN 4017337050871



### Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Do not operate the device near flammable materials or heat sources.
- Children and unauthorized persons must not operate or misuse the device.
- Do not block or cover the ventilation slots to prevent overheating.
- If visible damage or malfunctions occur, immediately stop operation and have the device inspected.
- Clean the device only when it is switched off and disconnected from the power supply.
- Use only original spare parts and accessories approved for this device.
- Do not place hot food or open containers with liquids inside the device to avoid condensation and icing issues.
- The refrigerant is flammable.
- If the cooling circuit is damaged, immediately switch off the device, disconnect it from the power supply, and ventilate the room. Avoid open flames or sparks.
- Do not use mechanical devices or tools to speed up the defrosting process, as this could damage the cooling circuit.
- Repairs and maintenance must only be carried out by qualified personnel.

Origin China

customs tariff no. 84185090

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827