

TECHNICAL DATA SHEET

Order No. **323-3108**

Item/Model **SARO Ventilated Bakery Freezer
model B 800 BT**

GTIN **4017337036608**



- **Material: (housing and interior) stainless steel**
- **Door self-closing, lockable**
- **With 10 runners**
- **For W 600 x D 800 mm (or 2 x W 600 x D 400 mm) grids**
- **Supplied without grids/plates**
- **Interior lighting**
- **Heated door frame to prevent condensation**
- **Digital temperature control (DIXELL)**
- **Insulation: 65 mm**
- **Forced air cooling**
- **Automatic defrost**
- **Temp. -18 / -22 °C**
- **Connection: 230 V - 50 Hz - 0.675 kW**
- **Capacity (gross/net): 852 / 534 liters**
- **Internal dimensions: W 624 x D 861.5 x H 1410 mm**
- **External dimensions: W 740 x D 990 x H 2010 mm**
- **Weight: 170kg**
- **Refrigerant: R290**
- **Energy efficiency class: D (spectrum A+++ to G) with climate class 5**
-> high-performance device!
- **Sound level: approx. 48dB(A)**

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. **323-3108**

Item/Model **SARO Ventilated Bakery Freezer
model B 800 BT**

GTIN **4017337036608**



Safety and Warning Instructions

- Place the device exclusively on a stable, level surface.
- Ensure that the mains voltage matches the specifications on the rating plate.
- Children and unauthorized persons must not operate or misuse the device.
- Never clean the device with a water jet to avoid the risk of short circuits.
- After transporting the device, it must remain upright for at least 24 hours before being switched on to prevent damage to the refrigerant circuit.
- Do not operate the device near heat sources, direct sunlight, or in damp environments.
- Maintain a minimum distance of 10 cm from the back wall and 30 cm from the top for proper ventilation.
- The ventilation area must always be free of dust and obstructions to ensure optimal cooling performance.
- The refrigerant is flammable – avoid damage to the cooling circuit. In case of a leak, ventilate the room thoroughly and avoid open flames or sparks.
- If visible damage or malfunctions occur, immediately stop operation and contact the authorized dealer.
- Before cleaning, maintenance, or extended periods of non-use, unplug the device and fully defrost it.
- Regularly clean the condenser slots to remove dust buildup and maintain efficiency.
- Repairs and maintenance must only be performed by qualified personnel.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827