

TECHNICAL DATA SHEET

Order No. 446-1005

Item/Model SARO Wine cooling cabinet
model WK 162 D

GTIN 4017337042296



- Material: (housing) steel powder coated, black; (interior) plastic, black
- Glass door, lockable
- Door with Low-E glass for less energy loss
- With inverter compressor, performance is based on required refrigeration demand
- Digital Control
- Insulation: 50 mm
- 2 climate zones, setting of only one zone also possible
- 7 wooden grids for approx. 154 standard bottles
- LED-lighting (white), separately switchable
- Double forced air cooling
- Automatic defrost
- Temperature zone 1: +5 / +12 °C; Zone 2: +12 / +20 °C
- Connection: 230 V - 50 Hz - 0,180 kW
- Capacity: 379 liters
- External dimensions: W 595 x D 710 x H 1720 mm
- Weight: 99 kg
- Refrigerant: R600a
- Energy efficiency class: G (spectrum A to G)

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827

SAFETY & WARNING INSTRUCTIONS

Order No. 446-1005

Item/Model SARO Wine cooling cabinet
model WK 162 D

GTIN 4017337042296



Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure the mains voltage matches the specifications on the nameplate.
- Children and unauthorized persons must not operate or be unsupervised near the device.
- Immediately discontinue use if visible damage or malfunctions occur, and contact qualified personnel.
- Do not place the device near heat sources or in direct sunlight, as this may affect efficiency.
- Keep ventilation openings clean and unobstructed to avoid overheating.
- Never clean the device with a water jet or immerse it in liquids to prevent short circuits and electric shock.
- The refrigerant is flammable. Avoid damaging the cooling circuit to minimize the risk of leaks.
- After transporting the device, let it stand still for 24 hours before connecting it to the power supply to allow the refrigerant to settle.
- The device is intended exclusively for wine storage. Do not store flammable, explosive, or unsuitable substances in it.
- Repairs must only be performed by qualified personnel using original spare parts.
- Dispose of packaging materials safely and keep them out of the reach of children to prevent choking hazards.
- Do not turn on the device if it has become wet. Have it inspected by a professional before the next use.
- Operating the device in very humid or poorly ventilated areas may impair functionality and cause damage.
- Regularly inspect the power cord for damage and have it replaced by qualified personnel if necessary.
- Do not make changes to the temperature switches or ventilation openings during operation to ensure proper functionality.
- Unplug the device and ensure all moving parts have stopped before cleaning or maintenance.
- When loading and unloading, ensure no objects block the ventilation openings or the fan.

Origin China

customs tariff no. 84181020

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 * Geschäftsführer: Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827