

## TECHNICAL DATA SHEET

Order No. **323-4235**

Item/Model **SARO Bar cooler with 2 glass doors  
and 2 drawers  
model BC 3100 G S2**

GTIN **4017337071982**



- Material: (housing) steel powder-coated, black; (interior) light metal
- 2 glass doors (door hinge not reversible) and 2 drawers with glass
- 4 height adjustable shelves
- 6 height adjustable feet
- Digital temperature control (DIXELL)
- Insulation: 40 mm
- Circulating air cooling
- Automatic defrost
- Temperature range: +2 / +8 °C
- Connection: 220 V - 50 Hz - 0,320 kW
- Shelves: 4x W 430 x D 395 mm
- Capacity: 537 liters
- Interior dimensions: W 1622 x D 415 x H 720 mm
- Exterior dimensions: W 2002 x D 513 x H 860 mm
- Weight (net/gross): 135 / 164 kg
- Refrigerant: R600a
- Energy efficiency class: C (spectrum A to G)

Origin China

customs tariff no. 0

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827

## SAFETY & WARNING INSTRUCTIONS

Order No. **323-4235**

Item/Model **SARO Bar cooler with 2 glass doors  
and 2 drawers  
model BC 3100 G S2**

GTIN **4017337071982**



### Safety and Warning Instructions

- Place the device only on a stable, level, and non-slip surface.
- Ensure that the mains voltage corresponds to the information on the nameplate.
- After transport or significant tilting, allow the device to stand upright for at least 24 hours before switching it on to prevent damage to the cooling system.
- Do not block ventilation slots and openings to avoid overheating and inefficient cooling.
- Children and unauthorized persons must not operate the device or be left unsupervised near it.
- Do not store flammable, explosive, or chemical substances inside the device.
- Never immerse the device in water or clean it with a water jet to avoid the risk of short circuits and electric shock.
- Always switch off the device, unplug it, and allow it to cool completely before cleaning or maintenance.
- Open doors and drawers only as long as necessary to minimize energy loss.
- Use only original spare parts and accessories approved for the device.
- Do not place hot food or uncovered liquids inside the device to prevent condensation or icing problems.
- The refrigerant is flammable; in case of a leak, ventilate the room thoroughly and avoid open flames.
- After a power outage or unplugging, wait at least 5 minutes before switching the device back on to prevent damage to the compressor.
- Repairs and maintenance must only be carried out by qualified personnel.
- Immediately stop operation if visible damage or malfunctions occur, and contact your retailer or qualified personnel.

Origin China

customs tariff no. 0

Importer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Klevé HRB 2768 \* Geschäftsführer: Dominique de Charry, Aloys de Charry  
ID-Nr. DE 120061194 \* St.-Nr. 116/5718/0194 \* ILN 4017337000005 \* WEEE-Reg.-Nr. DE 58229827