



GENERAL DETAILS

- Rack dimensions: **50x50 cm**
- Total weight: 95 Kg
- Washing cycles / racks/hour: 90"-120"/ 40-30
- Possibility of automatic start of washing cycle by closing the hood
- Upper and lower rotating wash/rinse arms made of composite materials
- Wash pump: 550 W
- Boiler capacity: 5 lt
- Tank capacity: 20 lt
- Boiler heating elements: 6,0 kW
- Tank heating elements: 2,4 kW
- Water quantity per cycle: 2,0 lt
- Electromechanical control panel
- Useful washing height: 425 mm
- Magnetic hood microswitch
- Automatic filling of water
- Adjustable rinse-aid dispenser
- Hot rinse
- Thermostop-controlled rinse operating temperature
- Anti-Backflow system on the hydraulic circuit included

WATER FILTRATION

- Pre-filtering of tank water by means of no. 1 stainless steel filter
- Single wash pump filter, easily removable

BODY

- AISI 304 stainless steel body
- Wash tank with rounded corners
- Single skin hood
- Hood opening system with springs
- Removable upper and lower wash/rinse arms for easy cleaning
- Boiler in AISI 304 stainless steel

EQUIPMENT

- 1 rack 50x50 cm, 12/18 plates
- 1 glass rack 50x50 cm
- 1 cutlery basket
- 1 inlet hose (2 m length)
- 1 drain hose (2,5 m length)

OPTIONALS

- Drain pump
- Electric detergent dispenser
- 60 Hz version
- Kit booster pump

ACCESSORIES

- Entry/exit tables in stainless steel
- Pre-wash tables in stainless steel
- Special baskets

INSTALLATION

- Use the screws of the feet and a spirit level to ensure that the machine is levelled

MAIN POWER SUPPLY

- The voltage of main power supply must be compatible with the rated voltage
- The machine must be connected to a suitable earth (ground) system
- Connect the machine power socket to the multi-pole wall switch provided

WATER SUPPLY CONNECTION

- A water softener must be installed if the water is hard
- The water pressure must be between 0.2MPa (2 bar), and, 0.5MPa (5 bar)
- The temperature of the water-supply must be between 10°C to 50°C

TECHNICAL SPECIFICATIONS

- Voltage:
380-415V3N/220-240V3/ 220-240V ~50 Hz
- Total power: **6,55 kW**
- Amperage: **10 A / 16 A / 28 A**
- Powered cord supply size: **5x2,5 / 3x4 mmq**

WH 720 PA

